NSN 5915-00-726-4387

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-726-4387

| Overall Height: |
|--|
| 3.440 inches |
| Body Length: |
| 2.250 inches |
| Body Width: |
| 2.000 inches |
| Body Height: |
| 3.060 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.690 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.440 inches |
| Reference Frequency Per Function: |
| 1.75 kilohertz blank |
| Input Impedance Per Function W/load: |
| 10.0 kilohms blank |
| Output Impedance Per Function W/source Across Input: |
| 10.0 kilohms blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 1.0 blank |
| Functional Terminal Type And Quantity: |
| 1 solder stud input 1st function |
| Specified Frequencies Of Discrimination Per Function: |
| 0.00 hertz blank and 3.50 kilohertz blank and 5.00 kilohertz blank and 10.00 kilohertz blank |
| Thread Size: |
| 0.138 inches |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 0.00 hertz blank and 3.50 kilohertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 1.0 blank and 1.0 blank and 50.0 blank and 50.0 blank |
| Body Surface Treatment: |

Tin

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-00-726-4387

Low Pass Filter - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0