

View Online at <https://aerobasegroup.com/nsn/5915-00-726-8700>

Body Length:

Between 1.719 inches and 1.781 inches

Body Width:

Between 1.219 inches and 1.281 inches

Body Height:

Between 3.469 inches and 3.531 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.234 inches and 1.266 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.734 inches and 0.766 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Reference Frequency Per Function:

1.5 kilohertz blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

900.00 hertz blank and 1.00 kilohertz blank and 2.00 kilohertz blank and 2.20 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

1.00 kilohertz blank and 2.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 1.0 blank and 1.0 blank and 3.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0