

View Online at <https://aerobasegroup.com/nsn/5915-00-726-8700>

**Body Length:**

Between 1.719 inches and 1.781 inches

**Body Width:**

Between 1.219 inches and 1.281 inches

**Body Height:**

Between 3.469 inches and 3.531 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.234 inches and 1.266 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.734 inches and 0.766 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Reference Frequency Per Function:**

1.5 kilohertz blank

**Input Impedance Per Function W/load:**

10.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

900.00 hertz blank and 1.00 kilohertz blank and 2.00 kilohertz blank and 2.20 kilohertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

1.00 kilohertz blank and 2.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 1.0 blank and 1.0 blank and 3.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0