NSN 5915-00-728-5982

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-728-5982

| Overall Length: |
|---|
| 3.062 inches |
| Overall Height: |
| 1.500 inches |
| Overall Width: |
| 1.000 inches |
| Body Length: |
| 2.312 inches |
| Body Width: |
| 1.000 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.438 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.438 inches |
| Operating Tempurature Range: |
| -40.0/+80.0 degrees celsius |
| Reference Frequency Per Function: |
| 2.85 megahertz blank |
| Input Impedance Per Function W/load: |
| 200.0 ohms blank |
| Output Impedance Per Function W/source Across Input: |
| 200.0 ohms blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 6.0 blank |
| Functional Terminal Type And Quantity: |
| 2 pin ground 3rd function |
| Specified Frequencies Of Discrimination Per Function: |
| 2.65 megahertz blank and 2.80 megahertz blank and 2.90 megahertz blank and 3.05 megahertz blank |
| Thread Size: |
| 0.112 inches |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 2.80 megahertz blank and 2.90 megahertz blank |

52.0 blank and 3.0 blank and 52.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

NSN 5915-00-728-5982

Band Pass Filter - Page 2 of 2



| Style | De | siar | nato | r |
|-------|----|-------|------|---|
| , | | v. 9. | | |

Rectangular terminal/terminals on adjacent surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0