

View Online at <https://aerobasegroup.com/nsn/5915-00-754-9579>

Overall Height:

2.969 inches

Body Length:

1.719 inches

Body Width:

1.219 inches

Body Height:

2.531 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.234 inches and 1.266 inches

Vibration Resistance Range In Hertz:

+10.0/+300.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.734 inches and 0.766 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

50.0 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

25.00 hertz blank and 48.50 hertz blank and 51.50 hertz blank and 100.00 hertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

48.50 hertz blank and 51.50 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

35.0 blank and 2.0 blank and 2.0 blank and 35.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0