

View Online at <https://aerobasegroup.com/nsn/5915-00-754-9579>

**Overall Height:**

2.969 inches

**Body Length:**

1.719 inches

**Body Width:**

1.219 inches

**Body Height:**

2.531 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.234 inches and 1.266 inches

**Vibration Resistance Range In Hertz:**

+10.0/+300.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.734 inches and 0.766 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

50.0 hertz blank

**Source Impedance Rating Per Function:**

10.0 kilohms blank

**Load Impedance Per Function:**

10.0 kilohms blank

**Input Impedance Per Function W/load:**

10.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

25.00 hertz blank and 48.50 hertz blank and 51.50 hertz blank and 100.00 hertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

48.50 hertz blank and 51.50 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

35.0 blank and 2.0 blank and 2.0 blank and 35.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0