

View Online at <https://aerobasegroup.com/nsn/5915-00-756-9678>

**Overall Height:**

2.625 inches

**Body Length:**

1.719 inches

**Body Width:**

1.219 inches

**Body Height:**

2.281 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.125 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.625 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

5.85 kilohertz blank

**Input Impedance Per Function W/load:**

10.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

**Average Power Rating Per Function:**

0.225 watts blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.95 kilohertz blank and 2.61 kilohertz blank and 3.90 kilohertz blank and 7.80 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

3.90 kilohertz blank and 7.80 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

40.0 blank and 45.0 blank and 1.0 blank and 1.0 blank

**Maximum Dielectric Withstanding Dc Voltage:**

50.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0