

View Online at <https://aerobasegroup.com/nsn/5915-00-756-9678>

Overall Height:

2.625 inches

Body Length:

1.719 inches

Body Width:

1.219 inches

Body Height:

2.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.125 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

5.85 kilohertz blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Average Power Rating Per Function:

0.225 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.95 kilohertz blank and 2.61 kilohertz blank and 3.90 kilohertz blank and 7.80 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

3.90 kilohertz blank and 7.80 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 45.0 blank and 1.0 blank and 1.0 blank

Maximum Dielectric Withstanding Dc Voltage:

50.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0