## NSN 5915-00-760-0663

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-760-0663

Overall Height:
0.990 inches
Body Length:
2.250 inches
Body Width:
1.000 inches
Body Height:
0.640 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.950 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.700 inches
Operating Tempurature Range:
-20.0/+85.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
500.0 kilohertz blank
Source Impedance Rating Per Function:
75.0 ohms blank
Load Impedance Per Function:
75.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 terminal
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
2 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
0.00 hertz blank and 1.00 megahertz blank and 2.00 megahertz blank and 3.00 megahertz blank
Frequency Band Width Per Function:
0.00 hertz blank and 1.00 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
1.0 blank and 3.0 blank and 30.0 blank and 60.0 blank
Style Designator:
Pactangular terminal/terminals on one surface

Rectangular terminal/terminals on one surface

## NSN 5915-00-760-0663

Low Pass Filter - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0

