NSN 5915-00-760-0675

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-760-0675

| Overall Height: |
|---|
| 0.950 inches |
| Body Length: |
| 2.250 inches |
| Body Width: |
| 1.000 inches |
| Body Height: |
| 0.640 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.950 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+2000.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.700 inches |
| Operating Tempurature Range: |
| -20.0/+85.0 degrees celsius |
| Average Life Rating In Hours: |
| 10000.0 |
| Reference Frequency Per Function: |
| 3.3 megahertz blank |
| Source Impedance Rating Per Function: |
| 75.0 ohms blank |
| Load Impedance Per Function: |
| 75.0 ohms blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 terminal |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 1.5 blank |
| Functional Terminal Type And Quantity: |
| 4 pin ground 3rd function |
| Specified Frequencies Of Discrimination Per Function: |
| 1.30 megahertz blank and 2.00 megahertz blank and 4.60 megahertz blank and 7.10 megahertz blank |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 2.00 megahertz hlank and 4.60 megahertz hlank |

40.0 blank and 1.0 blank and 1.0 blank and 40.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

NSN 5915-00-760-0675

Band Pass Filter - Page 2 of 2



| Sty | yle | Desig | gna | tor |
|-----|-----|-------|-----|-----|
| _ | | | | |

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0