

View Online at <https://aerobasegroup.com/nsn/5915-00-762-0579>

**Overall Length:**

5.500 inches

**Overall Height:**

1.000 inches

**Body Width:**

1.234 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Reference Frequency Per Function:**

48.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Input Terminal Manufacturer Code:**

70998

**Input Terminal Identification:**

4240-156

**Output Terminal Manufacturer Code:**

70998

**Output Terminal Identification:**

4240-156

**Voltage Standing Wave Ratio Per Function:**

1.4 blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.5 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

20.00 megahertz blank and 76.00 megahertz blank and 125.00 megahertz blank and 1.50 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

20.00 megahertz blank and 76.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

0.5 blank and 0.5 blank and 60.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

20.0 megahertz blank and 76.0 megahertz blank

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0