NSN 5915-00-762-2435

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-762-2435

Overall Height:
1.656 inches
Body Length:
1.500 inches
Body Width:
1.500 inches
Body Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.063 inches
Operating Tempurature Range:
+15.0/+50.0 degrees celsius
Reference Frequency Per Function:
41.66 hertz blank
Input Impedance Per Function W/load:
1.0 kilohms blank
Output Impedance Per Function W/source Across Input:
1.0 kilohms blank
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Inclosure Type:
Inclosure Type: Encased
Encased
Encased Mounting Facility Type And Quantity:
Encased Mounting Facility Type And Quantity: 2 threaded hole
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi):
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels:
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity:
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Frequency Band Width Per Function:
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Frequency Band Width Per Function: 0.00 hertz blank and 83.33 hertz blank
Encased Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Frequency Band Width Per Function: 0.00 hertz blank and 83.33 hertz blank Style Designator:
Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Frequency Band Width Per Function: 0.00 hertz blank and 83.33 hertz blank Style Designator: Rectangular terminal/terminals on one surface
Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Frequency Band Width Per Function: 0.00 hertz blank and 83.33 hertz blank Style Designator: Rectangular terminal/terminals on one surface Shelf Life:
Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Frequency Band Width Per Function: 0.00 hertz blank and 83.33 hertz blank Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a
Mounting Facility Type And Quantity: 2 threaded hole Screw Thready Qty Per Inch (tpi): 40 Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Frequency Band Width Per Function: 0.00 hertz blank and 83.33 hertz blank Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a

NSN 5915-00-762-2435

Low Pass Filter - Page 2 of 2



Fiig:

A047b0