

View Online at <https://aerobasegroup.com/nsn/5915-00-763-5088>

Overall Height:

3.360 inches

Body Length:

4.500 inches

Body Width:

1.250 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.160 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.562 inches

Operating Temperature Range:

-55.0/+75.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

90.0 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

2.0 kilohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

8.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

88.00 kilohertz blank and 89.00 kilohertz blank and 91.00 kilohertz blank and 92.00 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

89.00 kilohertz blank and 91.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 6.0 blank and 6.0 blank and 20.0 blank

Special Features:

Carrier frequency 88.0 khz upper sideband

Unpackaged Unit Weight:

1.300 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

00724-08-00242-008 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0