

View Online at <https://aerobasegroup.com/nsn/5915-00-763-5092>

Overall Height:

3.360 inches

Body Length:

4.500 inches

Body Width:

1.810 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.160 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.750 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.562 inches

Operating Temperature Range:

-55.0/+75.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

78.0 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

2.0 kilohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

8.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

75.50 kilohertz blank and 76.00 kilohertz blank and 80.00 kilohertz blank and 80.50 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

76.00 kilohertz blank and 80.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

5.0 blank and 1.0 blank and 1.0 blank and 55.0 blank

Unpackaged Unit Weight:

1.300 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

00724-08-00242-005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0