

View Online at <https://aerobasegroup.com/nsn/5915-00-763-7593>

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

1000.0

End Application:

Nimitz class cvn, oliver perry class ffg, austin ship class lpd-4 amphibious transport docks, wasp class lhd, emory s. Land class as, whidbey island class as, whidbey island class lsd, kidd class ddg, forrestal class cv, supply class aoe

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

1.0 blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

2500.0 volts dc blank

Thread Size:

0.375 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

5.0 kilovolts at sea level

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0