

View Online at <https://aerobasegroup.com/nsn/5915-00-763-7593>

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

1000.0

**End Application:**

Nimitz class cvn, oliver perry class ffg, austin ship class lpd-4 amphibious transport docks, wasp class lhd, emory s. Land class as, whidbey island class as, whidbey island class lsd, kidd class ddg, forrestal class cv, supply class aoe

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Operating Current Rating Per Function In Amps:**

1.0 blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unef

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

2500.0 volts dc blank

**Thread Size:**

0.375 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

5.0 kilovolts at sea level

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0