## NSN 5915-00-764-0067

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-764-0067

| View Online at https://aerobasegroup.com/nsn/5915-00-764-0067   |
|---|
| Overall Length:   |
| 8.312 inches  |
| Body Length:  |
| 7.812 inches  |
| Body Width:   |
| 5.750 inches  |
| Body Height:  |
| 2.500 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  |
| 7.000 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:   |
| 5.000 inches  |
| Operating Tempurature Range:  |
| +0.0/+50.0 degrees celsius  |
| Reference Frequency Per Function:   |
| 1.65 kilohertz blank  |
| Input Impedance Per Function W/load:  |
| 75.0 ohms blank   |
| Output Impedance Per Function W/source Across Input:  |
| 75.0 ohms blank   |
|   |
| Mounting Facility Screw Thread Series Designator:   |
| Mounting Facility Screw Thread Series Designator:<br>Unc  |
|   |
| Unc   |
| Unc<br>Inclosure Type:  |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole  |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:   |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank  |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:   |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank<br>Functional Terminal Type And Quantity:<br>1 connector, receptacle output 2nd function   |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank<br>Functional Terminal Type And Quantity:<br>1 connector, receptacle output 2nd function<br>Specified Frequencies Of Discrimination Per Function:  |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank<br>Functional Terminal Type And Quantity:<br>1 connector, receptacle output 2nd function<br>Specified Frequencies Of Discrimination Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank   |
| Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 6 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank   |
| Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 6 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank Thread Size: 0.112 inches   |
| Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 6 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank   |
| Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 6 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank Thread Size: 0.112 inches Body Material: Metal  |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank<br>Functional Terminal Type And Quantity:<br>1 connector, receptacle output 2nd function<br>Specified Frequencies Of Discrimination Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank<br>Thread Size:<br>0.112 inches<br>Body Material:<br>Metal<br>Frequency Band Width Per Function:  |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank<br>Functional Terminal Type And Quantity:<br>1 connector, receptacle output 2nd function<br>Specified Frequencies Of Discrimination Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank<br>Thread Size:<br>0.112 inches<br>Body Material:<br>Metal<br>Frequency Band Width Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank<br>Functional Terminal Type And Quantity:<br>1 connector, receptacle output 2nd function<br>Specified Frequencies Of Discrimination Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank<br>Thread Size:<br>0.112 inches<br>Body Material:<br>Metal<br>Frequency Band Width Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank |
| Unc<br>Inclosure Type:<br>Hermetically sealed<br>Mounting Facility Type And Quantity:<br>6 threaded hole<br>Insertion Loss At Reference Frequency Per Function In Decibels:<br>3.0 blank<br>Functional Terminal Type And Quantity:<br>1 connector, receptacle output 2nd function<br>Specified Frequencies Of Discrimination Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank and 3.80 kilohertz blank and 8.00 kilohertz blank<br>Thread Size:<br>0.112 inches<br>Body Material:<br>Metal<br>Frequency Band Width Per Function:<br>300.00 hertz blank and 3.00 kilohertz blank |

Terminals one surface

## NSN 5915-00-764-0067

Low Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0