

View Online at <https://aerobasegroup.com/nsn/5915-00-764-3119>

**Body Length:**

Between 2.480 inches and 2.520 inches

**Body Width:**

Between 1.100 inches and 1.140 inches

**Body Height:**

Between 1.480 inches and 2.020 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.600 inches and 1.640 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.730 inches and 0.770 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

2.0 1st radio interference

**Maximum Voltage Drop Per Function:**

750.0 millivolts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

72314-1076-642 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0