

View Online at <https://aerobasegroup.com/nsn/5915-00-767-0313>

**Overall Height:**

1.273 inches

**Body Length:**

2.800 inches

**Body Width:**

1.000 inches

**Body Height:**

1.038 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.300 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.500 inches

**Operating Temperature Range:**

+70.0/+90.0 degrees fahrenheit

**Average Life Rating In Hours:**

400000.0

**Reference Frequency Per Function:**

11.6125 megahertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

11.2375 megahertz blank and 11.5125 megahertz blank and 11.7125 megahertz blank and 11.9895 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

11.5125 megahertz blank and 11.7125 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

06845-4011351-0715 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0