

View Online at <https://aerobasegroup.com/nsn/5915-00-767-0943>

Overall Height:

4.562 inches

Body Length:

2.312 inches

Body Width:

2.000 inches

Body Height:

4.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.531 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.812 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.35 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.95 kilohertz blank and 2.20 kilohertz blank and 2.50 kilohertz blank and 2.60 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

2.20 kilohertz blank and 2.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0