## NSN 5915-00-768-4663

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-768-4663

**Overall Height:** 

4.438 inches

**Body Length:** 

Between 2.844 inches and 2.906 inches

**Body Width:** 

2.000 inches

**Body Height:** 

4.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

**Operating Tempurature Range:** 

+0.0/+50.0 degrees celsius

**Reference Frequency Per Function:** 

15.0 hertz blank

Input Impedance Per Function W/load:

100.0 kilohms blank

**Output Impedance Per Function W/source Across Input:** 

100.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Inclosure Type:** 

Hermetically sealed

**Mounting Facility Type And Quantity:** 

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

10.0 blank

**Functional Terminal Type And Quantity:** 

2 tab, solder lug ground 3rd function

**Specified Frequencies Of Discrimination Per Function:** 

0.00 hertz blank and 30.00 hertz blank and 0.00 hertz blank and 30.00 hertz blank

Thread Size:

0.138 inches

**Frequency Band Width Per Function:** 

0.00 hertz blank and 30.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.5 blank and 10.0 blank and 35.0 blank and 35.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

## NSN 5915-00-768-4663

Low Pass Filter - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A047b0