

View Online at <https://aerobasegroup.com/nsn/5915-00-772-5293>

**Overall Length:**

4.375 inches

**Overall Height:**

0.750 inches

**Body Length:**

3.375 inches

**Body Width:**

1.266 inches

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.875 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.875 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Reference Frequency Per Function:**

300.0 megahertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

1.38 blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.4 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

200.00 megahertz blank and 400.00 megahertz blank and 520.00 megahertz blank and 1.48 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

200.00 megahertz blank and 400.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 1.0 blank and 58.0 blank and 58.0 blank

**Body Surface Treatment:**

Silver

**Precious Material And Location:**

Surface silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0