

View Online at <https://aerobasegroup.com/nsn/5915-00-774-6454>

Overall Height:

Between 3.407 inches and 3.531 inches

Body Length:

Between 4.063 inches and 4.125 inches

Body Width:

Between 1.438 inches and 1.500 inches

Body Height:

Between 2.969 inches and 3.031 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.500 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

Operating Temperature Range:

-28.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

80.0 kilohertz blank

Input Impedance Per Function W/load:

100.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 megohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

79.20 kilohertz blank and 79.65 kilohertz blank and 80.35 kilohertz blank and 80.80 kilohertz blank

Thread Size:

0.164 inches

Body Material:

Metal

Frequency Band Width Per Function:

79.65 kilohertz blank and 80.35 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0