

View Online at <https://aerobasegroup.com/nsn/5915-00-774-6454>

**Overall Height:**

Between 3.407 inches and 3.531 inches

**Body Length:**

Between 4.063 inches and 4.125 inches

**Body Width:**

Between 1.438 inches and 1.500 inches

**Body Height:**

Between 2.969 inches and 3.031 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.812 inches

**Operating Temperature Range:**

-28.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

80.0 kilohertz blank

**Input Impedance Per Function W/load:**

100.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1.0 megohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

79.20 kilohertz blank and 79.65 kilohertz blank and 80.35 kilohertz blank and 80.80 kilohertz blank

**Thread Size:**

0.164 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

79.65 kilohertz blank and 80.35 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0