

View Online at <https://aerobasegroup.com/nsn/5915-00-775-4063>

Overall Length:

4.750 inches

Overall Height:

3.500 inches

Overall Width:

4.750 inches

Body Length:

3.750 inches

Body Width:

4.250 inches

Body Height:

Between 3.470 inches and 3.530 inches

Unthreaded Mounting Hole Diameter:

Between 0.205 inches and 0.215 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.250 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.250 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

60.0 hertz blank

Source Impedance Rating Per Function:

60.0 ohms blank

Load Impedance Per Function:

60.0 ohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.15 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 320.00 hertz blank and 2.00 kilohertz blank and 4.00 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 320.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 35.0 blank and 35.0 blank

Special Features:

Terminals on one surface

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0