

View Online at <https://aerobasegroup.com/nsn/5915-00-775-4063>

**Overall Length:**

4.750 inches

**Overall Height:**

3.500 inches

**Overall Width:**

4.750 inches

**Body Length:**

3.750 inches

**Body Width:**

4.250 inches

**Body Height:**

Between 3.470 inches and 3.530 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.205 inches and 0.215 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.250 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

3.250 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

60.0 hertz blank

**Source Impedance Rating Per Function:**

60.0 ohms blank

**Load Impedance Per Function:**

60.0 ohms blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.15 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 320.00 hertz blank and 2.00 kilohertz blank and 4.00 kilohertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 320.00 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 35.0 blank and 35.0 blank

**Special Features:**

Terminals on one surface

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0