

View Online at <https://aerobasegroup.com/nsn/5915-00-782-8902>

**Overall Length:**

2.875 inches

**Overall Height:**

1.093 inches

**Overall Width:**

0.500 inches

**Body Length:**

2.125 inches

**Body Width:**

0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.093 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.875 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-20.0/+55.0 degrees celsius

**Average Life Rating In Hours:**

2500.0

**Reference Frequency Per Function:**

500.0 kilohertz blank

**Source Impedance Rating Per Function:**

2.3 kilohms blank

**Load Impedance Per Function:**

2.3 kilohms blank

**Input Impedance Per Function W/load:**

2.3 kilohms blank

**Output Impedance Per Function W/source Across Input:**

2.3 kilohms blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.0 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

400.00 kilohertz blank and 490.00 kilohertz blank and 510.00 kilohertz blank and 600.00 kilohertz blank

**Body Material:**

Metal



**Frequency Band Width Per Function:**

490.00 kilohertz blank and 510.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

40.0 blank and 1.0 blank and 1.0 blank and 40.0 blank

**Body Surface Treatment:**

Silver

**Special Features:**

Terminals on one surface

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0