

View Online at <https://aerobasegroup.com/nsn/5915-00-797-7654>

Overall Height:

2.078 inches

Body Width:

2.016 inches

Body Height:

1.766 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.656 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

5.0 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

800.0 ohms blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

400.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 10.00 kilohertz blank and 20.00 kilohertz blank and 30.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

0.00 hertz blank and 10.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0