NSN 5915-00-802-7977

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-802-7977

Body Length:
1.688 inches
Body Width:
1.188 inches
Body Height:
2.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Reference Frequency Per Function:
100.0 hertz blank
Source Impedance Rating Per Function:
10.0 kilohms blank
Load Impedance Per Function:
10.0 kilohms blank
Input Impedance Per Function W/load:
10.0 kilohms blank
Output Impedance Per Function W/source Across Input:
10.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Inclosure Type:
Inclosure Type: Hermetically sealed
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches Frequency Band Width Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches Frequency Band Width Per Function: 200.00 hertz blank and 200.00 hertz blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches Frequency Band Width Per Function: 200.00 hertz blank and 200.00 hertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches Frequency Band Width Per Function: 200.00 hertz blank and 200.00 hertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 35.0 blank and 35.0 blank and 6.0 blank and 6.0 blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches Frequency Band Width Per Function: 200.00 hertz blank and 200.00 hertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 35.0 blank and 35.0 blank and 6.0 blank and 6.0 blank Style Designator:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches Frequency Band Width Per Function: 200.00 hertz blank and 200.00 hertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 35.0 blank and 35.0 blank and 6.0 blank Style Designator: Rectangular terminal/terminals on one surface
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 0.0 blank Specified Frequencies Of Discrimination Per Function: 0.00 hertz blank and 134.00 hertz blank and 200.00 hertz blank and 200.00 hertz blank Thread Size: 0.138 inches Frequency Band Width Per Function: 200.00 hertz blank and 200.00 hertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 35.0 blank and 35.0 blank and 6.0 blank and 6.0 blank Style Designator: Rectangular terminal/terminals on one surface Shelf Life:

NSN 5915-00-802-7977

High Pass Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0