

View Online at <https://aerobasegroup.com/nsn/5915-00-804-6849>

Overall Height:

Between 3.126 inches and 3.249 inches

Body Length:

Between 2.719 inches and 2.781 inches

Body Width:

Between 2.344 inches and 2.406 inches

Body Height:

Between 2.782 inches and 2.843 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.094 inches and 2.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.719 inches and 1.781 inches

Reference Frequency Per Function:

750.0 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 1.50 kilohertz blank and 2.25 kilohertz blank and 4.50 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 1.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 35.0 blank and 35.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0