NSN 5915-00-805-1972

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-805-1972

Overall Length:

5.952 inches

Body Length:

3.938 inches

Body Outside Diameter:

2.234 inches

Vibration Resistance Range In Hertz:

+5.0/+500.0

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

50.0 blank

Maximum Voltage Drop Per Function:

0.75 volts screw on tube not specified and 0.75 volts 23rd band suppression not specified

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab w/screw input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

250.0 volts at sea level and 150.0 volts at altitude

Operating Voltage Rating And Type Per Function:

130.0 volts ac blank and 400.0 volts dc blank

Thread Size:

1.125 inches

Maximum Dielectric Withstanding Dc Voltage:

800.0 volts at sea level

Special Features:

Includes one mtg bracket with slot

Style Designator:

Round terminal/terminals on opposite surfaces

NSN 5915-00-805-1972

Radio Frequency Interference Filter - Page 2 of 2



Sh	elf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0