## NSN 5915-00-810-9028

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-810-9028

Overall Height:
2.875 inches
Body Length:
1.688 inches
Body Width:
1.188 inches
Body Height:
2.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Reference Frequency Per Function:
2.0 kilohertz blank
Source Impedance Rating Per Function:
600.0 ohms blank
Load Impedance Per Function:
500.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
0.0 blank
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Specified Frequencies Of Discrimination Per Function:
0.00 kilohertz blank and 4.00 kilohertz blank and 6.00 kilohertz blank and 6.00 kilohertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:
0.00 kilohertz blank and 4.00 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 35.0 blank and 35.0 blank

## NSN 5915-00-810-9028

Low Pass Filter - Page 2 of 2



Style Designator:
Rectangular terminal/terminals on one surface
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0