NSN 5915-00-814-8934

Radio Frequency Interference Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5915-00-814-8934 |
|--|
| Overall Length: |
| 2.000 inches |
| Body Length: |
| Between 1.250 inches and 1.374 inches |
| Body Outside Diameter: |
| Between 0.639 inches and 0.701 inches |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Average Life Rating In Hours: |
| 250.0 |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Power Line Frequency Rating Per Function In Hertz: |
| 400.0 blank |
| Operating Current Rating Per Function In Amps: |
| 2.0 blank |
| Mounting Facility Screw Thread Series Designator: |
| Unf |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Functional Terminal Type And Quantity: |
| 1 wire lead input 1st function |
| Maximum Dielectric Withstanding Ac Rms Voltage: |
| 250.0 volts at sea level |
| Operating Voltage Rating And Type Per Function: |
| 125.0 volts ac blank and 300.0 volts dc blank |
| Thread Size: |
| 0.312 inches |
| Maximum Dielectric Withstanding Dc Voltage: |
| 100.0 volts at sea level |
| Style Designator: |
| Round terminal/terminals on opposite surfaces |
| Test Data Document: |
| 13499-241-7018-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5915-00-814-8934

Radio Frequency Interference Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0