

View Online at <https://aerobasegroup.com/nsn/5915-00-814-9334>

**Overall Height:**

Between 2.430 inches and 2.490 inches

**Body Length:**

Between 3.485 inches and 3.515 inches

**Body Width:**

Between 2.485 inches and 2.515 inches

**Body Height:**

Between 1.985 inches and 2.015 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.995 inches and 3.005 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.995 inches and 2.005 inches

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

98.250 kilohertz blank

**Source Impedance Rating Per Function:**

750.0 ohms blank

**Load Impedance Per Function:**

750.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

96.250 kilohertz blank and 96.750 kilohertz blank and 99.750 kilohertz blank and 100.250 kilohertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

96.750 kilohertz blank and 99.750 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

70.0 blank and 6.0 blank and 6.0 blank and 70.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

08440-200-0025 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0