

View Online at <https://aerobasegroup.com/nsn/5915-00-814-9334>

Overall Height:

Between 2.430 inches and 2.490 inches

Body Length:

Between 3.485 inches and 3.515 inches

Body Width:

Between 2.485 inches and 2.515 inches

Body Height:

Between 1.985 inches and 2.015 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.995 inches and 3.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.995 inches and 2.005 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

98.250 kilohertz blank

Source Impedance Rating Per Function:

750.0 ohms blank

Load Impedance Per Function:

750.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

96.250 kilohertz blank and 96.750 kilohertz blank and 99.750 kilohertz blank and 100.250 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

96.750 kilohertz blank and 99.750 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 6.0 blank and 6.0 blank and 70.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

08440-200-0025 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0