

View Online at https://aerobasegroup.com/nsn/5915-00-818-3391

Overall Length:
3.220 inches
Body Length:
2.188 inches
Body Outside Diameter:
0.750 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Power Line Frequency Rating Per Function In Hertz:
1.0 blank
Operating Current Rating Per Function In Amps:
1.0 blank and 1.0 blank
Maximum Voltage Drop Per Function:
1.25 volts ac blank
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
······································
1 threaded bushing
1 threaded bushing
1 threaded bushing Functional Terminal Type And Quantity:
<ol> <li>threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>tab, solder lug output 2nd function</li> </ol>
<ol> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> </ol>
<ol> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>400.0 volts ac blank and 130.0 volts dc blank</li> </ol>
<ul> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>400.0 volts ac blank and 130.0 volts dc blank</li> <li>Style Designator:</li> </ul>
<ul> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>400.0 volts ac blank and 130.0 volts dc blank</li> <li>Style Designator:</li> <li>Round terminal/terminals on opposite surfaces</li> </ul>
<ul> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>400.0 volts ac blank and 130.0 volts dc blank</li> <li>Style Designator:</li> <li>Round terminal/terminals on opposite surfaces</li> <li>Shelf Life:</li> </ul>
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 400.0 volts ac blank and 130.0 volts dc blank Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 400.0 volts ac blank and 130.0 volts dc blank Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 400.0 volts ac blank and 130.0 volts dc blank Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 400.0 volts ac blank and 130.0 volts dc blank Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 400.0 volts ac blank and 130.0 volts dc blank Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: No