## NSN 5915-00-820-2768

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-820-2768

**Overall Length:** 

**2.735** inches

**Body Length:** 

Between 1.906 inches and 2.094 inches

**Body Outside Diameter:** 

Between 0.813 inches and 0.937 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

**Operating Tempurature Range:** 

-55.0/+95.0 degrees celsius

**Source Impedance Rating Per Function:** 

50.0 ohms blank

**Load Impedance Per Function:** 

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:** 

400.0 blank

**Operating Current Rating Per Function In Amps:** 

2.0 blank

**Maximum Voltage Drop Per Function:** 

0.6 volts dc blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

**Maximum Tempurature Rise:** 

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:** 

Unf

Inclosure Type:

Hermetically sealed

**Mounting Facility Type And Quantity:** 

1 threaded bushing

**Features Provided:** 

Nut and washer

**Functional Terminal Type And Quantity:** 

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

230.0 volts at sea level

**Operating Voltage Rating And Type Per Function:** 

125.0 volts ac blank and 400.0 volts dc blank

**Thread Size:** 

0.4375 inches

**Body Material:** 

Metal

## NSN 5915-00-820-2768

Radio Frequency Interference Filter - Page 2 of 2



Maximum Dielectric Withstanding Dc Voltage:	Maximum	Dielectric	Withstanding	Dc	Voltage:
---	---------	------------	--------------	----	----------

800.0 volts at sea level

**Style Designator:** 

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0