

View Online at <https://aerobasegroup.com/nsn/5915-00-824-4085>

Overall Height:

2.460 inches

Body Length:

1.500 inches

Body Width:

1.500 inches

Body Height:

2.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

-20.0/+80.0 degrees celsius

Reference Frequency Per Function:

400.0 hertz blank

Source Impedance Rating Per Function:

13.0 kilohms blank

Load Impedance Per Function:

100.0 kilohms blank

Input Impedance Per Function W/load:

13.0 kilohms blank

Output Impedance Per Function W/source Across Input:

100.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encapsulated

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Specified Frequencies Of Discrimination Per Function:

300.00 hertz blank and 380.00 hertz blank and 420.00 hertz blank and 550.00 hertz blank

Thread Size:

0.112 inches

Body Material:

Plastic

Frequency Band Width Per Function:

380.00 hertz blank and 420.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

28.0 blank and 3.0 blank and 3.0 blank and 28.0 blank

Unpackaged Unit Weight:

8.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

97942-579r629 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0