

View Online at <https://aerobasegroup.com/nsn/5915-00-835-4956>

Body Length:

2.500 inches

Body Width:

1.750 inches

Body Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.938 inches

Vibration Resistance Range In Hertz:

+5.0/+33.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.219 inches

Operating Temperature Range:

-0.0/+50.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

200.0 kilohertz blank

Source Impedance Rating Per Function:

8.2 kilohms blank

Load Impedance Per Function:

8.2 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

199.80 kilohertz blank and 199.95 kilohertz blank and 200.05 kilohertz blank and 200.20 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

199.95 kilohertz blank and 200.05 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0