

View Online at <https://aerobasegroup.com/nsn/5915-00-840-0601>

Overall Length:

3.344 inches

Body Length:

2.750 inches

Body Width:

1.375 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Reference Frequency Per Function:

312.5 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Input Terminal Manufacturer Code:

80058

Input Terminal Identification:

Ug-1464/u

Output Terminal Manufacturer Code:

80058

Output Terminal Identification:

Ug-1464/u

Voltage Standing Wave Ratio Per Function:

1.4 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

175.00 megahertz blank and 200.00 megahertz blank and 225.00 megahertz blank and 400.00 megahertz blank

Thread Size:

0.086 inches

Frequency Band Width Per Function:

225.00 megahertz blank and 400.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 5.0 blank and 1.0 blank and 1.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

225.0 megahertz blank and 400.0 megahertz blank

Body Surface Treatment:

Silver

Special Features:

Terminals on one surface, 0.656 in. O/a body h

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0