

View Online at https://aerobasegroup.com/nsn/5915-00-841-9182

Overall Length:
4.109 inches
Body Length:
3.000 inches
Body Outside Diameter:
1.125 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
2.0 blank and 2.0 blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Marine fracility Ocean Theory I Ocean Design at an
Mounting Facility Screw Thread Series Designator:
Unef
Unef
Unef Inclosure Type:
Unef Inclosure Type: Hermetically sealed
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity:
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size:
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.625 inches
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.625 inches Shelf Life:
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.625 inches Shelf Life: N/a
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.625 inches Shelf Life: N/a
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.625 inches Shelf Life: N/a Unit Of Measure:
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.625 inches Shelf Life: N/a Unit Of Measure:
Unef Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 250.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.625 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No