

View Online at <https://aerobasegroup.com/nsn/5915-00-843-8046>

Overall Height:

2.190 inches

Body Length:

Between 1.250 inches and 1.310 inches

Body Width:

Between 1.250 inches and 1.310 inches

Body Height:

Between 1.620 inches and 1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.880 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.880 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

50.0 hertz blank

Input Impedance Per Function W/load:

2.0 kilohms blank

Output Impedance Per Function W/source Across Input:

2.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encapsulated

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 200.00 hertz blank and 280.00 hertz blank and 285.00 hertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

1.00 hertz blank and 200.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.6 blank and 3.0 blank and 10.0 blank and 10.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0