NSN 5915-00-843-8046

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-843-8046

Overall Height: 2.190 inches **Body Length:** Between 1.250 inches and 1.310 inches **Body Width:** Between 1.250 inches and 1.310 inches **Body Height:** Between 1.620 inches and 1.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.880 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.880 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius Average Life Rating In Hours: 10000.0 **Reference Frequency Per Function:** 50.0 hertz blank Input Impedance Per Function W/load: 2.0 kilohms blank **Output Impedance Per Function W/source Across Input:** 2.0 kilohms blank Mounting Facility Screw Thread Series Designator: Unc **Inclosure Type:** Encapsulated Mounting Facility Type And Quantity: 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank **Functional Terminal Type And Quantity:** 1 tab, solder lug output 2nd function **Specified Frequencies Of Discrimination Per Function:** 1.00 hertz blank and 200.00 hertz blank and 280.00 hertz blank and 285.00 hertz blank **Thread Size:** 0.138 inches **Frequency Band Width Per Function:** 1.00 hertz blank and 200.00 hertz blank **Discrimination At Specificationified Frequencies Per Function In Decibels:** 0.6 blank and 3.0 blank and 10.0 blank and 10.0 blank Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level

NSN 5915-00-843-8046

Low Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0