

View Online at <https://aerobasegroup.com/nsn/5915-00-846-0066>

Overall Height:

2.813 inches

Body Length:

1.626 inches

Body Width:

1.625 inches

Body Height:

2.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.188 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.188 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

8.5 kilohertz blank

Source Impedance Rating Per Function:

1.0 kilohms blank

Load Impedance Per Function:

1.0 kilohms blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

12.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

5.80 kilohertz blank and 7.90 kilohertz blank and 9.20 kilohertz blank and 12.00 kilohertz blank

Thread Size:

0.164 inches

Frequency Band Width Per Function:

7.90 kilohertz blank and 9.20 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

26.0 blank and 3.0 blank and 3.0 blank and 26.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0