

View Online at <https://aerobasegroup.com/nsn/5915-00-846-0829>

Overall Height:

3.000 inches

Body Length:

3.000 inches

Body Width:

2.000 inches

Body Height:

2.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.500 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

3.495 kilohertz blank

Source Impedance Rating Per Function:

33.0 kilohms blank

Load Impedance Per Function:

33.0 kilohms blank

Input Impedance Per Function W/load:

33.0 kilohms blank

Output Impedance Per Function W/source Across Input:

33.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

12.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.499 kilohertz blank and 3.295 kilohertz blank and 3.695 kilohertz blank and 5.495 kilohertz blank

Thread Size:

0.164 inches

Frequency Band Width Per Function:

3.295 kilohertz blank and 3.695 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0