

View Online at <https://aerobasegroup.com/nsn/5915-00-846-3723>

Overall Height:

1.508 inches

Body Length:

1.895 inches

Body Width:

1.457 inches

Body Height:

1.208 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.380 inches and 1.420 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.500 inches and 0.540 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

403.8 kilohertz blank

Input Impedance Per Function W/load:

1.5 kilohms blank

Output Impedance Per Function W/source Across Input:

1.5 kilohms blank

Principal Circuitry Type Per Function:

Inductance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

394.80 kilohertz blank and 402.30 kilohertz blank and 405.30 kilohertz blank and 412.80 kilohertz blank

Thread Size:

0.086 inches

Frequency Band Width Per Function:

402.30 kilohertz blank and 405.30 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

15.0 blank and 3.0 blank and 3.0 blank and 15.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0