

View Online at <https://aerobasegroup.com/nsn/5915-00-850-8992>

**Overall Height:**

Between 3.258 inches and 3.565 inches

**Body Length:**

Between 2.187 inches and 2.312 inches

**Body Width:**

Between 1.937 inches and 2.062 inches

**Body Height:**

Between 2.938 inches and 3.125 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.677 inches and 1.697 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.427 inches and 1.447 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Average Life Rating In Hours:**

2500.0

**Reference Frequency Per Function:**

1.6875 kilohertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

2.0 megohms blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

17.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.5 blank

**Functional Terminal Type And Quantity:**

2 wire hook ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

1.625 kilohertz blank and 1.6625 kilohertz blank and 1.7125 kilohertz blank and 1.75 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.6625 kilohertz blank and 1.7125 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

20.0 blank and 3.0 blank and 3.0 blank and 20.0 blank

**Unpackaged Unit Weight:**

2.000 pounds

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0