

View Online at <https://aerobasegroup.com/nsn/5915-00-851-8844>

**Overall Height:**

2.732 inches

**Body Length:**

2.400 inches

**Body Width:**

2.100 inches

**Body Height:**

2.400 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.900 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.600 inches

**Operating Temperature Range:**

-55.0/+65.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.955 kilohertz blank

**Source Impedance Rating Per Function:**

600.0 ohms blank

**Load Impedance Per Function:**

600.0 ohms blank

**Input Impedance Per Function W/load:**

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

600.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

1 standard tube base input-output/ground

**Specified Frequencies Of Discrimination Per Function:**

1.775 kilohertz blank and 1.9125 kilohertz blank and 1.9975 kilohertz blank and 2.165 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.9125 kilohertz blank and 1.9975 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

25.0 blank and 2.5 blank and 2.5 blank and 25.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0