

View Online at <https://aerobasegroup.com/nsn/5915-00-853-0395>

Overall Height:

Between 1.876 inches and 2.000 inches

Body Length:

2.550 inches

Body Width:

2.250 inches

Body Height:

Between 1.594 inches and 1.656 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.845 inches and 1.907 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.595 inches and 1.657 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Reference Frequency Per Function:

3.55 kilohertz blank

Source Impedance Rating Per Function:

50.0 kilohms blank

Load Impedance Per Function:

50.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

15.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

3.535 kilohertz blank and 3.549 kilohertz blank and 3.551 kilohertz blank and 3.565 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

3.549 kilohertz blank and 3.551 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

2.0 blank and 20.0 blank and 20.0 blank and 2.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0