NSN 5915-00-855-2839

220.00 megahertz blank and 400.00 megahertz blank

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-855-2839

Overall Length:
6.094 inches
Overall Height:
1.156 inches
Body Length:
4.438 inches
Body Width:
1.156 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
5.000 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Reference Frequency Per Function:
310.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.35 blank
Average Power Rating Per Function:
150.0 watts blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
220.00 megahertz blank and 400.00 megahertz blank and 1.825 gigahertz blank and 2.00 gigahertz blank
Body Material:
Metal
Frequency Band Width Per Function:

NSN 5915-00-855-2839

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 80.0 blank and 80.0 blank

Body Surface Treatment:

Silver

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0